Sub A1

1. A method comprising:

forming a circuit element over a triple well in a substrate; and

biasing a well of said triple well through a resistor.

2. The method of claim 1 including forming an integrated inductor over a triple well.

3. The method of claim 1 including forming a P-type well in an N-type well formed in said substrate.

4. The method of claim 3 including biasing the N-type and P-type wells through different resistors.

5. The method of claim 1 including providing a common bias potential to different wells through separate resistors for each well.

A

6. The method of claim 5 including forming a radio frequency circuit element over a triple well.

7. The method of claim 5 including biasing said wells through resistors having a resistance greater than one hundred ohms.

8. The method of claim 7 including forming a complementary metal oxide semiconductor transistor over a triple well and biasing at least one of the wells of said triple well through a resistor.

9. The method of claim 1 including forming a plurality of triple wells in said substrate and forming a circuit element over each of said triple wells, biasing at least one well of each of said triple wells through a common potential, each of said potentials being applied to said wells through a resistor.

10. The method of claim 9 including applying a supply potential to said plurality of wells through a resistor.

11. An integrated circuit comprising:

a substrate;

a circuit element formed over said substrate;

a triple well formed in said substrate under said circuit element; and

a resistor connectable to a bias potential and coupled to a well of said triple well.

12. The circuit of claim 11 wherein the triple well each includes a P-well formed in an N-well formed in the substrate.

13. The circuit of claim 11 wherein said resistor is coupled to a supply voltage.

14. The circuit of claim 11 including a plurality of circuit elements formed over said substrate, each of said circuit elements formed over a triple well, each of said triple wells having at least one well connectable to a bias potential.

15. The circuit of claim 14 including a resistor coupled to each of said wells, each of said resistors connectable to a bias potential so as to supply resistance in the path of said bias potential to said well.

16. The circuit of claim 15 wherein the same potential is applied to a plurality of wells.

17. The circuit of claim 16 wherein said plurality of resistors are connectable to the same bias source.

18. The circuit of claim 17 wherein each of said resistors is connectable to a supply voltage.

19. The circuit of claim 16 wherein each of said resistors is connected to a path that is common with the path of each of the other resistors coupled to wells.

Sub A27

20. A method comprising:

forming a first circuit element over a triple well in a substrate;

biasing a first well of said first triple well through a first resistor with a first bias potential;

forming a second circuit element over a second triple well in a substrate; and

biasing a second well of said second triple well through a second resistor coupled to said first bias potential.

21. The method of claim 20 including coupling the first bias potential to said first and second wells through a common trace to a supply potential.

22. The method of claim 20 including forming an integrated inductor over the first triple well.

23. The method of claim 20 including forming a P-type well and an N-type well formed in said substrate.

24. The method of claim 23 including biasing the N-type and P-type wells through different resistors.

25. The method of claim 20 including forming a radio frequency element over said first triple well.

26. The method of claim 25 including biasing said wells through resistors having a resistance greater than 100 ohms.

27. An integrated circuit comprising:

a substrate;

a first circuit element formed over said substrate;

a first triple well formed in said substrate under said first circuit element;

a first resistor connectable to a first bias potential and coupled to a first well of said first triple well;

a second circuit element formed over said substrate;

a second triple well formed in said substrate under said second circuit element; and

a second resistor connectable to the first bias potential and coupled to the second well of said second triple well.

28. The circuit of claim 27 wherein said first circuit element is a complementary metal oxide semiconductor transistor.

29. The integrated circuit of claim 27 wherein said first circuit element is an integrated inductor.

30. The integrated circuit of claim 27 wherein said first bias potential is a supply voltage.

add A4